

# 4K60p UHD HDMI Splitters



**AE-1X4HDR-CEC-01**  
1x4 4K HDMI Splitter




**AE-1X8HDR-CEC-01**  
1x8 4K HDMI Splitter

## 4K60p HDMI & CEC Splitters

Take high definition audio and video from a single HDMI source device, such as BrightSign media players, and distribute it to multiple UHD TVs, UHD displays or UHD projectors using Augustus Enterprises proven UHD HDMI Splitters.

- Augustus HDMI splitters are specially designed for the unique requirements of retail and commercial installations for digital signage and TV demonstration where the highest quality video signal must be maintained
- Support resolutions up to 4096x2160p @ 60Hz frame rates
- Support HDR, HDR10 and Dolby Vision color at up to 18Gbps
- Splitters are available in 1x2, 1x4 and 1x8 input/output configurations
- Designed to distribute CEC commands of the source device to multiple displays
- Metal construction with secure mounting brackets



## 4K60p HDMI Cables

HDMI cables are NOT all the same. Many cables pass UHD, but they do not support all color depths and frame rates.

Our heavy duty, braided HDMI cables are designed and tested to work with all resolutions and frame rates of our HDMI splitters. Available in 3m, and 6.1m lengths.

# 4K60p UHD HDMI Splitter Specifications

<b>Model No.</b>	<b>AE-1X8HDR-CEC-01</b>	<b>AE-1X4HDR-CEC-01</b>	<b>AE-1X2HDR-CEC-01</b>
<b>Product Description</b>	4K HDR HDMI 2.0 Splitter 1x8	4K HDR HDMI 2.0 Splitter 1x4	4K HDR HDMI 2.0 Splitter 1x2
<b>HDCP Version</b>	HDCP 2.2		
<b>Input channel</b>	1 HDMI port		
<b>Output channel</b>	8 HDMI port	4 HDMI port	2 HDMI port
<b>Video format</b>	4K@60Hz/4K@30Hz/1080P/1080i/720p/576p/576i/480P/480i Supports HDR,HDR10 and Dolby Vision		
<b>Cascade</b>	Support One Layer		
<b>Deep color</b>	24bit, 30bit, 36bit		
<b>Audio format</b>	Dolby HD/DTS HD/Dolby Atmos/Dolby AC3/DTS/LPCM Etc.		
<b>Max Transmission bandwidth</b>	600MHz		
<b>Max Transmission rate</b>	18Gbps		
<b>Input cable length</b>	2160P/AWG 26 ≤5m; 1080P/AWG 26 ≤10m		
<b>Output cable length</b>	2160P/AWG 26 ≤5m; 1080P/AWG 26 ≤12m		
<b>Power adapter specification</b>	Input: AC 100~240V / Output: DC 5V/2A		
<b>Max Working Current</b>	1000mA		
<b>Working Temperature Range</b>	-5° ~ +40°C		
<b>Working Humidity Range</b>	5 to 85%RH (No Condensation)		
<b>Storage Temperature</b>	-15° to 55°C		
<b>Storage Humidity</b>	5 ~95%RH (No Condensation)		
<b>Housing Material</b>	Metal		
<b>Size</b>	280*136*25 (mm)	139*64*22 (mm)	96*53*21 (mm)
<b>Weight</b>	882g	220g	220g
<b>Included Accessories</b>	Power Adaptor		