

# 8-PORT 4K UHD HDMI SPLITTER with BrightSign Built-In

AUGUSTUS

SERIES 662025-662031



**BrightSign®**  
Built-In

Combines 8-Port 4K UHD HDMI splitter with BrightSign Built-In SoC offering an all-in-one solution for media player, splitter, audio switching and much more in a small form factor.


- Output up to 8 displays from a single source
- I/O Control CEC, RS232, UDP, TCP/IP
- A HDMI port designated as an external input for the splitter
- Detect “live” HDMI connection for status update
- Supports 4K@60Hz
- HDMI output (HS144 supports 2.0a) with CEC
- CEC control passthrough on all HDMI outputs
- Mainstream HTML5 Engine
- Highly reliable media handling platform
- 100baseT Ethernet
- S/PDIF digital audio
- Interactive controls: GPIO, UDP, 2x USB 2.0, RS232 Serial
- Wi-Fi & Bluetooth
- Supports daisy-chain 8-port splitter(s) for 22 HDMI ports
- BrightSign SoC obtains splitter(s) status via RS232
- Auto downscale output to 1080p by port



# 8-PORT 4K UHD HDMI SPLITTER with BrightSign Built-In

**AUGUSTUS**

Model No.	662025	662026	662030	662031
Product Description	8-Port 4K UHD HDMI Splitter with Built-in BrightSign SoC			
HDCP Version	HDCP 2.2			
BrightSign SoC	HS144 (4K UHD)		HS124 (1080p)	
Input Channel	1-Port HDMI			
Output Channel	8-Port HDMI			
Video Codecs	H.264, H.265, MPEG-2, MPEG-1			
Video Containers	.ts .mov .mp4 .mkv .mpg .vob .m2ts		.ts .mov .mp4 .mpg .vob .m2ts	
Color Space	SDR, HDR10		SDR	
Supported Video Resolutions	4096x2160, 3840x2160, 3840x600@60/59.94/50/30/29.97/25/24/23.9 8p; 1920x1200, 1920x1080@60/59.94/50/30 /29.97/24/23.98p; 1920x1080@60/59.94/50i; 1600x1200@60p; 1440x1050@75/60p; 1440x900@75/60p; 1360x768@60p; 1280x1024@75/60p; 1280x960@60p; 1280x800@75/60p; 1280x768@60p; 1280x720@60/59.94/50p; 1024x768@60p; 800x600@75/60p; 720x576@50p/50i; 720x480@60/59.94p/60i; 640x480@60p		1920x1200, 1920x1080@60/59.94/50/30/29.97/25/24/23.9 8p; 1920x1080@60/59.94/50i; 1600x1200@60p; 1440x1050@75/60p; 1440x900@75/60p; 1360x768@60p; 1280x1024@75/60p; 1280x960@60p; 1280x800@75/60p; 1280x768@60p; 1280x720@60/59.94/50p; 1024x768@60p; 800x600@75/60p; 720x576@50p/50i; 720x480@60/59.94p/60i; 640x480@60p	
Color Depth	8bit, 10bit or 12bit			
Audio Format	MP2, MP3, AAC and WAV (AC3, Dolby Atmos and DTS in Passthrough)			
Cascade	Support Two Layers of 8-Port Cascaded Splitters			
Max Transmission Bandwidth	600MHz			
Max Transmission Rate	18Gbps			
Input Cable Length	2160p/AWG 26 ≤5m, 1080p/AWG 26 ≤10m			
Output Cable Length	2160p/AWG 26 ≤5m, 1080p/AWG 26 ≤12m			
Power Adapter Specification	Input: AC 100-240V / Output: DC 5V/3A 50-60 Hz			
Max Working Current	1000mA			
Working Temperature Range	-5° to 40°C			
Working Humidity Range	5 to 85%RH (No Condensation)			
Storage Temperature	-15° to 55°C			
Storage Humidity	5 to 95%RH (No Condensation)			
Housing Material	Metal			
Size	280x136x25 (mm) / 11x5.35x1 (inches) Approx			
Weight	Splitter 1,190g / 2 lb 10 oz Power Supply 170g / 6 oz			
Included Accessories	Captivated Power Adapter			
Wi-Fi / Bluetooth	802.11a/b/g/n/ac Bluetooth® 4.0		802.11a/b/g/n/ac Bluetooth® 4.0	



**BrightSign**  
Built-In

**AUGUSTUS**

Augustus Enterprises, LLC.

55 Grant Street

Ramsey, NJ 07446

201.786.0404

201.786.0410 Fax

sales@augustusenterprises.com

www.augustusenterprises.com

© 2022, Augustus Enterprises, LLC. All other company names and products are trademarks or registered trademarks of their respective companies. We reserve the right to introduce modifications without notice. Dimensions are approximate.

AE662025-31\_Series\_SpecSheet\_2022-11-05\_v10